




LIGHTBAR SPECIFICATION SHEET
PART No: 17378
DESCRIPTION : 21TRPL47MC-C109084

Cable : Quick Disconnect with 22' Cable
Mounting Kit : Metal Mounting kit LX Kit



Wire Color	Function	Notes
GRN/BLK	Level 1 (R65)	
WHT/BLK	Level 2 (Blue rear only)	
BLU/BLK	Turn Signal Right	
GRN/WHT	Turn Signal Left	
WHT	Arrowstick Flash	
BLU/WHT	Alley Light Flash	
BLK	Takedown Flash	
BLK/WHT	Alley Light Left	
RED	Arrowstick Left	
RED/WHT	Alley Light Right	
RED/BLK	Level 3 (Full Blue)	
ORG/BLK	Takedown Lights Steady Burn	
BLK/RED	Pattern Select	
GRN	Stop Lights	
ORG	Arrowstick Right	
BLU	Lightbar DIM	
RED 1,5mm ³	Positive Lightbar	
RED 1,5mm ³	Positive Lightbar	
RED 1,5mm ³	Positive Lightbar	
BLACK 1,5mm ²	Ground	
BLACK 1,5mm ²	Ground	
BLACK 1,5mm ²	Ground	
BLACK 1,5mm ²	Ground	

Notes:

- L1 = Level 1 (R65)
- L2 = Level 2 (Blue Rear Only)
- L3 = Level 3 (Full Blue Cycle Flash)
- L1 + L2 = Blue Front Only
- L1 + L3 = Level Blue Cycle Flash + Front White Cycle Flash
- L2 + L3 = Level Blue Cycle Flash + Rear Red Cycle Flash
- L1 + L2 + L3 = Level Blue Cycle Flash + Front White Cycle Flash + Rear Red Cycle Flash
- all functions are positive inputs
- Dim function dims the complete lightbar