



MC-Duo HD kit + connectors

P0050F0031-HD



Centralizing System

MC-DUO HD

Key benefits

- > Easy installation
- > Equipped for controlling all electrical appliances
- > Completely independent of existing electrical wiring
- > CANbus J1939 link (2x RJ45 5m)
- > Equipped with 2 control consoles

Characterize

- > Negative mass (housing)
- > 2 supply voltages possible
- > Automation and specific functions
- > Full Programmingbaarvia Console express
- > Arrowstick function (4 to 8 units)
- > Interlock possibility
- > Flash pattern function 90 cycles/min
- > Scene activation
- > Error recognition through monitoring
 - Open load
 - About load
 - Short Circuit
- > Standard equipped with DLI and Unitherm HD expansion
- > Compliance: E13*10R05 14763

Specifications

- > Operation Voltage: 10 to 30VDC (2x40A)
- > 12 static positive outputs (15A and 1x25A configurable)
- > 2 static independent negative outputs (1,5A)
- > 2 positive inputs
- > 2 negative inputs
- > 1 analog input
- > Ambient temperature -25°C to +60°C
- > MC Duo HD Central Unit :
 - Weight 595 gr
 - Dimensions 177 x 105 x 45 mm
- > Main console (with foot) :
 - Weight 115 gr
 - Dimensions 91 x 70 x 28 mm
- > Secondary Console (Panel mount) :
 - Weight 115 gr
 - Dimensions 91 x 70 x 28 mm