




LIGHTBAR SPECIFICATION SHEET

PART No: 13796

DESCRIPTION : 21TRPL47MC-C53216

Cable : Quick Disconnect with 22' Cable

Mounting Kit : Metal Mounting kit LX Kit



Wire Color	Function	Notes
GRN/BLK	Level 1 (R65)	
WHT/BLK	Level 2 (Blue rear only)	
BLU/BLK	Rear-Cut-off	
GRN/WHT	Front Cut-off	
WHT	Arrowstick Flash	
BLU/WHT	Alley Light Flash	
BLK	Takedown Flash	
BLK/WHT	Left Alley Light	
RED	Arrowstick Left	
RED/WHT	Right Alley Light	
RED/BLK	Level 3 (Full Blue)	
ORG/BLK	Take down Lights Steady Burn	
BLK/RED	Pattern Select	
GRN	Cruise Lights	
ORG	Arrowstick Right	
BLU	Lightbar DIM	
RED 1,5mm ³	Positive Lightbar	
RED 1,5mm ³	Positive Lightbar	
RED 1,5mm ³	Positive Lightbar	
BLACK 1,5mm ²	Ground	
BLACK 1,5mm ²	Ground	
BLACK 1,5mm ²	Ground	
BLACK 1,5mm ²	Ground	

Notes:

- L1 = Level 1 (R65)
- L2 = Level 2 (Blue Rear Only)
- L3 = Level 3 (Full Blue Cycle Flash)
- L1 + L2 = Front Blue Only
- L1 + L3 = Level Blue Cycle Flash + Front White Flash
- all functions are positive inputs
- Dim function dims the complete lightbar