



TINY8
P0050F0008



TiNY8

Key benefits

- > Compact control panel for lighting and signalling applications.
- > Complete set of control panel, power module and FTP Bus cable(5m)
- > Control panel is equipped with backlighting and label collection

Designers

- > Interlock Function Blue Light/Siren
- > Interlock Function Blue Light/Grill Light
- > Handbrake-sensitive functions
- > Overview siren and flashing light status
- > Overview of 2 directional lighting functions
- > Overload protection
- > Flood protection
- > Reverse polarity protection

- > Push button control
- > Permanent outputs
- > Various Auto standby modes

- > Compliance: EMC 2004/104 e6 03 0331
ECE R10

- > Supplied materials

9	Vein end sleeve 2.5mm ²	Blue
9	Vein end sleeve 1.5mm ²	Red
> 1	Diode	MCC 1N4003

Specifications

- > Operational Voltage: from +9 to +28VDC
- > 8 positive outputs (10A each)
- > 2 negative outputs (-1.7A each)
- > 1 positive IGNITION input
- > 1 positive entry
- > 1 negative input
- > Terminal type:
 - Side supply voltage
8 x 0.8x6.35mm
 - Side FTP
8 x Screw clamp 3mm x 0.5mm
- > 1 FTP port for connection to control panel
- > Weight:
 - Power Module: 80gr.
1,76oz
 - Control panel: 30gr.
1.16oz
- > Dimensions:
 - Power Module: 94 x 73 x 26 mm (W x D x H)
3.7 x 2.9 x 1.02 inches (W x D x H)
 - Control panel: 81 x 39 x 24 mm (W x D x H)
3.2 x 1.5 x 0.95 inches (W x D x H)
- > Operating temperature: from -25°C to +60°C